

2.6 Hook-Block Combo

TFI hook-blocks are designed and manufactured according to API Spec 8C specification.

Model		YG90	YG135	YG170	YG225	YG315	YG450
API Load Rating	kN (lbs)	900 (200,000)	1350 (300,000)	1700 (380,000)	2250 (500,000)	3150 (700,000)	4,500 (1,000,000)
Sheaves Dia.	mm (in)	584 (23")	762 (30")	915 (36")	1117 (44")	1270 (50")	1524 (60")
Number of Sheaves	each	4	4	5	5	5	6
Drilling Line	mm (in)	26 (1")	26 (1")	29 (1-1/8")	32 (1-1/4")	35 (1-3/8")	38 (1-1/2")
Hook Opening	mm (in)	130 (5-1/8")	150 (5.9")	200 (7.9")	190 (7-1/2")	220 (8-5/8")	220 (8-5/8")
Overall Dimension (L x W x H)	mm (in)	2005×616×498 (79"×24"×20")	2946×838×647 (116"×33"×26")	3402×960×725 (134"×38"×29")	3714×1190×775 (146"×47"×31")	4191×1350×885 (165"×53"×35")	4887×1600×910 (192"×63"×36")
Weight	kg (lbs)	1250 (2756)	3126 (6892)	4594 (10,120)	6600 (14,550)	10,860 (23,892)	12,530 (27,624)

